

# AUDIO PATCH PRODUCTS

## TERMINATION PANELS



To obtain a quote:  
Call: +44 (0)1724 273224  
Email: sales@dem-uk.com

- 3 Pin XLR Connectors
- Female and/or Male Options
- Up to 3 x 16 Connectors
  
- High Visibility Clip-on Designation Strips
- Rigid Aluminium Alloy Extrusion
- Panel Colour Options



**OVERVIEW** - 2U and 3U Audio Termination Panels with 3 Pin XLR connectors as standard. Suitable for analogue or AES, these panels can also come supplied prewired to any of our other audio panels or just to a loom of a specified length.

**FEATURES** - Manufactured from robust aluminium alloy extrusion, this range has rows of 16 unified XLR cutouts, fitted as standard with male or female three pin latching XLR's. Each unit has one clip-on designation per row and two lacing bars.

**FINISH** - Standard Storm Grey powder coating for an excellent finish and robustness. Dawn Grey or Black also available.

Product Code	Description
ATP2216M	Audio Termination Panel 2U 2 x 16 XLR Male
ATP3316M	Audio Termination Panel 3U 3 x 16 XLR Male
ATP2216F	Audio Termination Panel 2U 2 x 16 XLR Female
ATP3316F	Audio Termination Panel 3U 3 x 16 XLR Female
ATP2216FM	Audio Termination Panel 2U 2 x 16 XLR Female & Male
ATP3316FM	Audio Termination Panel 3U 3 x 16 XLR Female & Male

\*\*Colour Options: SG (Storm Grey), DG (Dawn Grey) and BK (Black)

# AUDIO PATCH PRODUCTS

## PRE-WIRING



### Audio Pre-Wiring

Pre-wiring of audio jackfields can be carried out to customer specifications.

#### Typical requirements include:

- Overall Screened Cable
- Individually Screened Cable
- Half-normalled
- Fully-normalled
- Double-normalled
- Rear termination via loom, or attached to rear bracket
- Krone Connectors
- TAG Blocks
- EDACS

